

RAM MECHANICAL LOCKING STABILIZER CYLINDERS



Design Pressure

3000 PSI Working

Standard Bore Sizes

4.000 to 8.000 inches

Stroke Lengths

12 to 30 inches

Rod Diameters

3½ to 6 inches

Standard Port Types

NPT or Optional ORB

Specifications

- * Chrome Plated Hollow Shaft ASTM 513/519 Grade 1026/St52.3
- * Standard Mount Drilled Stub Shaft
- * Optional Mounts: Blank, Ball End and Custom Designed
- * Ductile Iron ASTM A536 (65-45-12) Piston and Head
- * Internal Thread Head
- * Assembly Bolts and Washers included
- * DOM Cylinder Tube ASTM 513/519 Grade 1026/St52.3
- * Honed Cylinder Tube for long seal life
- * Working Operating Pressure Rating of 3000 PSI
- * Lock Collar and Outer Mount Tube included
- * Tube Threaded with 4 TPI Acme Thread
- * Optional Split Nut available
- * 100% Hydraulic Bench Tested
- * Custom Designs available



Please contact RAM Engineering for dimensional data.

Ram Industries Inc.

33 York Road East

PO Box 5007

Yorkton SK S3N 3Z4 CANADA

Tel: 306.786.2677 Toll Free: 1.877.799.1005

Fax: 306.786.2651

sales@ramindustries.com www.ramindustries.com



ISO 9001:2008 Registered

Designers and Manufacturers of quality OEM and standard hydraulic and pneumatic cylinders